



FLOOR PLAN
SCALE: 1:100
579.0 GSM

GENERAL NOTES:

- A. INTERIOR PARTITIONS SHALL BE 200 MM CMU UNLESS NOTED OTHERWISE
- B. OPENINGS FOR DOORS SHALL BE LOCATED 200 MM FROM THE ADJACENT WALL UNLESS NOTED OTHERWISE
- C. SURFACES TO BE PAINTED SHALL BE CLEAN AND FREE OF FOREIGN MATTER BEFORE APPLICATION OF PAINT. CLEANING SHALL BE SCHEDULED SO THAT DUST AND OTHER CONTAMINANTS WILL NOT FALL ON WET, NEWLY PAINTED SURFACES.
- D. CONCRETE AND INTERIOR MASONRY SURFACES GROUTED SOLID SHALL BE ALLOWED TO DRY AT LEAST 30 DAYS BEFORE PAINTING EXCEPT CONCRETE SLAB ON GRADE WHICH SHALL BE ALLOWED TO CURE 90 DAYS BEFORE PAINTING.
- E. PAINTS CONTAINING LEAD IN EXCESS OF 0.06 PERCENT BY WEIGHT OF THE TOTAL NONVOLATILE CONTENT SHALL NOT BE USED.
- F. MERCURIAL FUNGICIDES SHALL NOT BE USED IN OIL-BASE PAINT.
- G. REMOVE LOOSE DIRT AND CLEAN SURFACES BEFORE PAINTING. APPLY PAINT TO INTERIOR STRUCTURAL RIGID FRAMINGS AND CEILINGS AND TEST FOR ADHESION. PRIMER COAT FOR MASONRY. INITIAL FIRST COAT WITH AN ACRYLIC LATEX PAINT FOR EXTERIOR SURFACES AND A SECOND COAT WITH A WATER REPELLENT ACRYLIC LATEX PAINT.
- H. METAL DOORS AND FRAMES SHALL RECEIVE A PRIMER COAT PLUS TWO COATS OF PAINT.
- I. DIMENSIONS ARE TO STRUCTURAL COLUMN GRID, EDGE OF WINDOW OPENINGS, AND TO HINGE SIDE OF DOOR OPENINGS.
- J. PROVIDE 1 HOUR RATED PARTITIONS AT STORAGE ROOM IN ACCORDANCE WITH NFPA 101, TABLE 28.3.2.2.2. FILL ANULAR SPACE AT ANY AND ALL PENETRATIONS IN FLOORS, WALLS, OR CEILINGS WITH APPROPRIATE FIRE STORING MATERIALS.

ROOM FINISHES:

- 1. WALLS: PAINTED PLASTER,
FLOOR: SEALED CONCRETE
CEILING: PAINTED PLASTER APPLIED TO STRUCTURE

KEY NOTES:

- 1. CONCRETE STOOP - RE: DETAIL 2/A6.
- 2. NOT USED
- 3. LINE OF ROOF OVERHANG ABOVE
- 4. TWO-PIECE WALL THIMBLE AND TRIM PLATE FOR OPTIONAL WOOD BURNING STOVE CHIMNEY PIPE. STOVE AND PIPE BY OTHERS.
- 5. PROVIDE FEC AT STORAGE ROOM IN ACCORDANCE WITH NFPA 101, 28.3.5.8.

LEGEND:

- (F.1.4) DOOR TYPE, SEE SHEET A5
- (A) WINDOW TYPE, SEE SHEET A5
- (X) KEY NOTE
- FEC FIRE EXTINGUISHER CABINET
- 1-HOUR RATED PARTITION
- (1) ROOM FINISH TYPE DESIGNATION
- DS METAL DOWNSPOUT

B13

UNLESS OTHERWISE NOTED, LINEAR DIMENSIONS SHOWN ARE IN MILLIMETERS (MM)
SCALE: 1: 100

SYMBOL	DESCRIPTION	DATE

DESIGNED BY: DLB	DATE: 09-30-09
DWN BY: AAR	SUBMITTED BY: BAKER
CHK BY: KRC	FILE NO: ANPSDA-101XXX

Michael Baker Corp.
A unit of Michael Baker Corporation
Attn: Business Park
1000 Franklin Blvd.
Harrisburg, PA 17108
www.mbakercorp.com

STANDARD DESIGN
BARRACK BUILDING, OPEN BAY (579 GSM)
WOOD FIRED HEAT OPTION
FLOOR PLAN

SHEET
REFERENCE
NUMBER:
A1